



Antifreeze EXL 50/50 Clear

Product Application:

Antifreeze EXL 50/50 Clear is a fully formulated ready to use SCA enhanced ethylene glycol based heavy duty diesel engine coolant.

Antifreeze EXL 50/50 Clear is formulated to provide excellent protection in all heavy duty cooling systems in all types of climates and conditions offering superior protection against overheating, freezing, corrosion, scale, and cavitation of critical pumps.

Antifreeze EXL 50/50 Clear is a fully formulated phosphate free, low silicate product ready to use in heavy duty diesel as well as automotive systems.

Features and Advantages:

- *Incorporate nitrite technology protecting against pitting
- *Compatible with other fully formulated coolants
- *Phosphate-free technology reducing scaling
- *Excellent corrosion protection for iron, steel, aluminum, brass & copper

Meets or exceeds the following specifications:

ASTM D 3306
 ASTM D45345
 ASTM D 4340
 ASTM D 6210
 CID A-A-52624
 Cummins 14603
 Detroit Diesel 93K217
 Freightliner 48-22880
 J.I. Case JIC501
 John Deere H24A2 / H24C2
 MTU 5048
 Navistar B1 Type II
 TMC RP 329
 Caterpillar
 Paccar (Peterbilt and Kenworth)
 Volvo/Mack

And other engines that can benefit from a phosphate-free, low silicate formula coolant

Typical Characteristics:

Specific Gravity (16/16°C)	1.067-1.077
Freezing Point, as is	-37°C (34°F)
Boiling Point, Reflux	163°C (325°C)
PH, 50% Volume Solution	10.0 – 11.0
Reserve Alkalinity	3.0 – 3.8
Foam Test	150 ml. / 5sec., Max
Color	Clear

Visit us at – www.beaconlubricants.com